



Wall indoor units

AERI | AEMI



Ionizer



Anti-corrosion protection - gold coating



Heating at a temp. of -20°C



3D DC Inverter



Wi-Fi ready



Multi compatibility



Biofilter



Anti-corrosion protection - gold coating



3D DC Inverter



Follow me function



Automatic operating mode



Wi-Fi ready

	Model	ACP-07CH21AEMI/I	ACP-09CH25AERI/I+	ACP-12CH35AERI/I+	ACP-18CH50AERI/I+
Indoor unit	Capacity (W)	2052	2638	3517	5275
	Capacity (W)	2346	2931	3810	5568
	Air flow (m ³ / h) - HI / MID / LOW	520 / 460 / 340	483 / 362 / 303	584 / 477 / 395	730 / 500 / 420
	Refrigerant	R32	R32	R32	R32
	Dehumidifying capacity (L / h)	1.0	1.0	1.2	1.8
	Noise - Sound Pressure (dB (A)) - HI / MID / LOW / SI	40 / 30 / 26 / 21	36.5 / 29 / 24 / 20	39.5 / 33 / 25 / 21	43 / 33.5 / 28 / 23
	Sound power level (dB)	≤ 54	≤ 55	≤ 55	≤ 57
	Packaging dimensions (mm)	870 x 270 x 360	875 x 285 x 380	875 x 285 x 380	1045 x 305 x 410
	Product dimensions (mm)	805 x 194 x 285	802 x 189 x 297	802 x 189 x 297	965 x 215 x 319
	Gross / net weight (kg)	9.5 / 7.5	11.1 / 8.6	11.1 / 8.6	14.2 / 10.9
Connection	Liquid phase pipe diameter	1 / 4"	1 / 4"	1 / 4"	1 / 4"
	Gas phase pipe diameter	3 / 8"	3 / 8"	3 / 8"	1 / 2"
Interconnect cable	Connection (mm ²)	4 x 1.5	4 x 1.5	4 x 1.5	4 x 1.5
	Power Supply	~220-240 V / 1 / 50 Hz; Outdoor unit			